



STROJNÍ ZÁVITNÍK SE ŠROUBOVITOU DRÁŽKOU 40°

Machine tap with right-hand spiral flutes 40°

 Maschinengewindebohrer mit 40° RSP, rechtsschneidend

 Maschi a macchina con taglienti elicoidali destri 40°


 Машинный метчик со спиральной канавкой 40°

 40° Helis Makina Kılavuzu

TYPE
H

2690


2680



OX

TiCN

d ₁	P	l ₁	l ₂	d ₂	a	z	∅	OX	TiCN
M 3	0,5	56	5	3,5	2,7	3	2,5	•	•
M 3,5	0,6	56	6	4	3	3	2,9	•	•
M 4	0,7	63	7	4,5	3,4	3	3,3	•	•
M 4,5	0,75	70	8	6	4,9	3	3,7	•	•
M 5	0,8	70	8	6	4,9	3	4,2	•	•
M 6	1	80	10	6	4,9	3	5	•	•
M 7	1	80	10	7	5,5	3	6	•	•
M 8	1,25	90	13	8	6,2	3	6,8	•	•
M 9	1,25	90	13	9	7	3	7,8	•	•
M 10	1,5	100	15	10	8	3	8,5	•	•



Řezné podmínky / Cutting conditions / V_c

P3.1	Cement, a nitr. / Case hardened and nitriding steels	3-5	3-5
P3.2	Zušlechtěné oceli / Heat-treated steels <1200N/mm ²	3-5	6-8
P3.3	Nástrojové oceli / Tool steels		3-5
K6.2	Tvárná a temper. litina / Spher. graphite and mall. cast iron		7-10
N8.2	Legovaný hliník / Aluminium alloys Si>10%		12-20